



**"M" Series 48, 60, 72 and 84" Rear Discharge Grooming Mowers**



Phoenix Line "M" Series Rear Discharge Grooming Mowers turn your tractor into a mowing machine. Available in 4 cutting widths from 48" to 84". Choose solid or pneumatic tires depending on your specific requirements. These mowers feature a heavy duty welded one piece deck and three overlapping blades with specially designed baffles for a clean smooth cut and even dispersion of clippings. Available in popular red or orange colors, the powder coat paint finish keeps you machine looking new long after the competition has faded away.

Standard features include:

- Solid or Pneumatic tires on heavy duty wheels with greasable roller bearings
- Series 4 PTO shaft by Eurocardan
- Adjustable lower links with floating or fixed positions
- Front anti scalping roller on 84" models( Available Option on other models) \* as shown in photograph
- Floating top hitch for smooth terrain tracking
- One step grease points without removing safety shields

Specifications	M48-A	M48-S	M60-A	M60-S	M72-A	M72-S	M84-A	M84-S
Mowing Width (Inches)	48		60		72		84	
Overall Width (Inches)	50		63		74		86	
Mowing Height (Inches)	.75-4.25		.75-4.25		.75-4.25		.75-4.25	
Number of Blades	3		3		3		3	
Deck Material Thickness (MM/Gauge)	4/8		4/8		4/8		4/8	
Discharge	Rear		Rear		Rear		Rear	
Hitch	Cat 1		Cat 1		Cat 1		Cat 1	
PTO Shaft Series	4		4		4		4	
PTO Power Required (HP)	10-30		20-40		30-50		40-60	
Optimum PTO Speed (RPM)	540		540		540		540	
Blade Tip Speed (FPM)	3130		2650		2240		2030	
Approximate Weight W/PTO (LBS)	392	410	432	450	472	490	816	860
Tire Configuration	Pneumatic	Solid	Pneumatic	Solid	Pneumatic	Solid	Pneumatic	Solid
Anti-Scalp Roller	Optional		Optional		Optional		Standard	

**Fast Forward Services, Inc.**

PO Box 754  
 Dunn, NC 28334-0754  
 919-902-0522